

<u><i>Item#</i></u>	<u><i>bullet weight</i></u>	<u><i>typical velocity</i></u>
SF9-95 RHFP	95gr.	1320fps.
SF9-100 RHFP	100gr.	1250fps.
SF9-110 RHFP	110gr.	1200fps.
SF9-115 RHFP	115gr.	1150fps.
SF357SIG-100 RHFP	100gr.	1450fps.
SF38-110 RHFP	110gr.	1050fps.
SF38-125 RHFP	125gr.	1025fps.
SF40-125 RHFP	125gr.	1200fps.
SF40-135 RHFP	135gr.	1175fps.
SF40-150 LIMITED	150gr.*	1120fps.
SF45-155 RHFP	155gr.	1150fps.
SF45-165 RHFP	165gr.	1075fps.
SF45-175 RHFP	175gr.	1020fps.
SF223-42 NTP	42gr.	2500-3500fps.
SF223-42 MTP	42gr.	2500-3500fps.
SF223-42 WTP	42gr.	2500-3500fps.
SF308-125 NTP	125gr.	2300-3200fps.++
SF7.62x39-123 NTP	123gr.	2000-2500fps.

RHFP Reduced Hazard Flat Point

NTP Narrow Taper Point

MTP Mid Taper Point

WTP Wide Taper Point

* For use in 1911 competition style guns

++ higher in Magnum calibers

Note: Hollow Point configurations available upon request

Prototypes being developed and tested:

- 12ga. Slugs , Breaching Rounds and Buckshot
- Special Duty™ law enforcement components
- GreenLine™ tungsten composite components
- Match Grade Rimfire components

Crimp Notice: Proper crimping is critical. A minimal taper crimp is suggested and over crimping can cause a fracture of the bullet at the case mouth resulting in bullet break-off. Since reloading practices are beyond our control, SinterFire®, Inc. disclaims all liability for damages that may result.